

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>A61C 7/00, 7/12</b>		<b>A1</b>	(11) International Publication Number: <b>WO 99/34747</b>
			(43) International Publication Date: 15 July 1999 (15.07.99)
(21) International Application Number: PCT/IL98/00593 (22) International Filing Date: 7 December 1998 (07.12.98) (30) Priority Data: 122807 30 December 1997 (30.12.97) IL (71) Applicant (for all designated States except US): CADENT LTD. [IL/IL]; Hamelacha Street 14, 60372 Or Yehuda (IL). (72) Inventors; and (75) Inventors/Applicants (for US only): TAUB, Eldad [IL/IL]; Topaz Street 11, 71908 Reut (IL). KOPELMAN, Avi [IL/IL]; Ido Street 8, 52233 Ramat-Chen (IL). (74) Agent: REINHOLD COHN AND PARTNERS; P.O Box 4060, 61040 Tel Aviv (IL).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  Published With international search report.	

(54) Title: VIRTUAL ORTHODONTIC TREATMENT

## (57) Abstract

A method for virtual orthodontic treatment is provided in which a virtual set of orthodontic components is associated, in a virtual space, with a first virtual three-dimensional image of teeth, and then by a set of rules which define the effect of the set of components' teeth, the effect of the virtual treatment can be computed. This virtual treatment can be used to predict the results of a real-life orthodontic treatment as to design such a treatment.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LR	Liberia	SD	Sudan		
DK	Denmark			SE	Sweden		
EE	Estonia			SG	Singapore		

## VIRTUAL ORTHODONTIC TREATMENT

### FIELD AND BACKGROUND OF THE INVENTION

The present invention is generally in the field of orthodontics.

An orthodontic treatment has the objects of moving and reorienting teeth for both functional or aesthetic purposes. In such a treatment, the orthodont  
5 places a variety of orthodontic components on the teeth including brackets, which are firmly fixed to the teeth, and other components including wires, tensioning springs, etc., which apply forces and moments on the teeth, through the brackets, thereby causing the teeth to move. A major problem facing the orthodont is to predict the final outcome of the orthodontic treatment. Another problem to focus  
10 is to define the proper placement of the brackets and to select the proper force-inducing components to best yield the desired outcome. Currently, the design and predicting of orthodontic treatment is based mainly on the orthodont's personal "*look and feel*" and prior experience skills. This approach is not only error prone but also varies from one individual to the other, which is obviously  
15 undesired.

There is accordingly a need in the art to provide the orthodont with a tool for visual demonstration, design or predicting of possible outcome of an orthodontic treatment. Provided by the invention are method and system therefor.

## GENERAL DESCRIPTION OF THE INVENTION

In the context of the present description and the appended claims, the term "*movement*" or "*moving*" refers to repositioning teeth, reorientating teeth, or both. The term "*orthodontic treatment*" refers to a treatment intended to move at least one tooth; namely, an orthodontic treatment should be understood as encompassing a procedure where all or only part of the teeth (e.g. teeth of one jaw, a group of teeth in a section of a jaw, etc.) are moved. Furthermore, the term "*orthodontic treatment*" refers both to a treatment intended to yield movement to reach a final, close to ideal outcome of the treatment as well as to an interim treatment yielding an interim position and orientation of the teeth. In other words, the term "*orthodontic treatment*" mentioned herein encompasses both a treatment from an initial stage, i.e. before the treatment began, through to a final stage; a treatment from an initial stage to an interim stage; as well as to a treatment from an interim stage to another interim or final stage.

The term "*virtual treatment*" (referred to also, occasionally as virtual orthodontic treatment) as used herein means an orthodontic treatment as simulated on a computer. A virtual treatment may use virtual components (i.e. 'component' in the virtual computer environment) such as brackets, wires, tensioning springs or rubber bands, corresponding to real components as used in a real life orthodontic treatment, but may also use components which are not normally used in real-life treatment; and also components used in real-life treatment but are used in the virtual treatment in a different manner. Thus, for example, a virtual orthodontic treatment may use wires which are not normally used in a real life orthodontic treatment; may use wires of a cross-section other than such used in a real-life orthodontic treatment; may combine wires and brackets in a manner whereby the brackets are biased towards a rotational movement around the axis of the wire which is usually not performed in a real-life orthodontic treatment; etc. It will therefore be understood that the result of virtual treatment is not necessarily the same as the actual real treatment.

In the following, a method and system for virtual treatment is disclosed. Manual systems may be used by an orthodont to examine various alternative treatment paradigms and compare them to one another so as to see which one will yield the best result. For example, the orthodont may compare a treatment where one or more teeth are extracted to another treatment where all teeth are left in tact. In addition, the system and method of the invention may allow also the orthodont to select the orthodontic components which he will eventually use in the real-life treatment, to predict the course, time and cost of the treatment. This will all be clarified from the disclosure below.

It will also become clear from the following disclosure, the orthodontic treatment may be made to resemble a real-life orthodontic treatment, although not necessarily so, and occasionally, the orthodontic treatment may use components or may apply a set of rules which are not directly applicable to real-life treatment.

The present invention provides, by one of its aspects, a method for virtual orthodontic treatment, comprising:

(a) providing a first virtual three-dimensional image indicative of a three-dimensional (3D) model of teeth from at least one jaw, the model being manipulable so as to allow its viewing from a desired direction;

(b) selecting a virtual set of orthodontic components, and associating the components with the teeth of said first image so as to obtain a second image of said 3D model with said components associated therewith;

(c) using a set of rules, including at least one rule, defining the effect of said set of components on said teeth, computing the manner of movement of the teeth as a result of said effect, so as to obtain a third image comprising the teeth model following the virtual treatment.

The set of orthodontic components selected in step (b) includes components which are capable of imparting movement between at least two teeth. For example, the set may include at least two brackets and a wire, may include

rubber bands or tensioning springs for forcing two teeth one against the other, etc. Typically, the set of orthodontic components includes for each jaw, typically, but not necessarily, about 5 to about 10 brackets in the case of a child's jaw, and between about 5 to about 16 in the case of an adult's jaw.

5           The set of orthodontic components may be represented as an image which is similar to the image of the real orthodontic component, as seen in real life. However, orthodontic component may also be represented by any other graphic representations. For example, the wire may be represented by a straight or curved line; a bracket may be represented by a rectangular frame, , etc.

10           In accordance with some embodiments of the invention, the set of components includes brackets and a wire and the rule dictates that eventually all slots which receive the wire will be aligned with the wire where the latter is arranged as a splined curve indicative of the desired result of the virtual treatment. In other words, in this case the wire represents the desired results of alignment of  
15 all slots following the virtual treatment. Thus, by such an embodiment a component which represents a real-life component, i.e. a wire, is used in a different manner than in a real-life treatment in that it dictates the result of the treatment. This embodiment thus illustrates a general principle in some embodiments of the invention that while in a real-life treatment components act in  
20 combination to apply forces on teeth and the movement is a result of such applied forces, in a virtual treatment of the invention, the components may also dictate the final result. However, this does not exclude a possibility, in accordance with some other embodiments of the invention, where the movement of the teeth is dictated by forces and moments, which in this case are the set of rules, which act on the  
25 teeth under influence of the different components.

Thus, as will be appreciated, occasionally, the component and the set of rules may be associated with one another. Taking the previously illustrated embodiment as an example, the component, which is a wire defining a splined curve, has with it an associated rule dictating that the brackets, with the associated

teeth, should move, vertically, but possibly also horizontally, so that all brackets will eventually be positioned such that their respective slots are on the splined curve defined by the wire. In addition to the desired final result, the set of rules may also stipulate the computational algorithm defining the manner of movement of the teeth to yield said final result.

The set of rules may also allow, for example, the removal of the tooth in certain circumstances. For example, in the case of crowding, i.e. insufficient space for all teeth to assume an ideal position and orientation (a position and orientation such that the apex of all teeth are essentially on one splined curve), an interfering tooth may be removed. The removal may, by one embodiment, be automatic; by another embodiment, the user may decide in such a case which tooth is to be removed.

As will be explained in greater detail below, the set of rules is not limited to a specific implementation. Thus, by way of example, the set of rules may be extracted from a static set of rule database, or by way of another example from a dynamic learning database holding a rule base that may be adjusted depending upon e.g. various characteristics of the individual patient that undergoes the treatment.

The purpose of the virtual orthodontic treatment may be to change the relative orientation of the teeth, to change a distance between the teeth, to alter the inter-occlusion of distance between teeth of opposite jaws, etc.

In accordance with one example, where the teeth are such that they do not fill the entire space in a jaw (namely with an edge of one tooth being in proximity to a neighbouring tooth), the set of rules may also allow the addition of a tooth, which may, in the case of a child's jaw, represent a tooth which has not yet grown or, in the case of an adult's jaw, a crown which may be implanted in a real -ife treatment.

Steps (b) and (c) may be repeated a plurality of times until obtaining a desired result of the virtual treatment. In a repeated step (b), a



component already selected in a previous step may associated with the teeth model in a different manner, e.g. applying it on a different tooth, orienting it on a tooth in a different manner, etc.; or new components may be selected, e.g. new brackets, new rubber bands, a different wire; etc.

5           The 3D teeth model may be of all teeth in a jaw, may be a model of teeth of both jaws, may be a model of part of the teeth of one or both jaws.

          The term "*associating*" as used herein denotes the entire range of combining orthodontic components with teeth and to typically (but not necessarily) in a manner that stimulates combination thereof in real life treatment.

10          Typical, but not exclusive examples, being: attaching brackets to teeth at different positions or orientations; fixing a wire into the bracket's wire-receiving slot; sliding the bracket and the wire one with respect to another, changing the angle of the wire-receiving slot within the bracket so as to change the torque or moment between the wire and the bracket; fixing a tensioning spring or band around two  
15          adjacent teeth; etc. The wire chosen within the framework of the virtual treatment may have various geometries, e.g. straight or spline-curved, and various cross-sectional shapes, e.g. circular, oval, rectangular, etc. (usually to track the ideal curvature of the teeth arrangement in a jaw).

          In accordance with another aspect of the invention, there is  
20          provided a method for designing orthodontic treatment of teeth from at least one jaw, comprising:

          (a) providing a virtual three-dimensional image indicative of a three-dimensional model of the teeth in a manner allowing manipulation of the model for viewing the model from a desired direction;

25          (b) selecting a virtual set of orthodontic components corresponding to those intended to be used in said orthodontic treatment and associating the components with the teeth of said first image so as to obtain a second image of said three-dimensional model with said components associated therewith in a manner representing the manner in which said components and the teeth may be

combined in said orthodontic treatment;

(c) using a set of rules, including at least one rule, defining the manner in which said components affect movement of the teeth, so as to obtain a third image comprising the teeth model after movement of the teeth affected by said components;

(d) repeating steps (a) and (c) until a desired third image is obtained, which desired third image represents a desired position and orientation of teeth following the orthodontic treatment;

(e) recording said second image which yields, following step (c), the desired third image and using it as a basis for designing the orthodontic treatment.

In addition to allowing a design of the treatment, the method in accordance with the second aspect may also be used to predict the length of the treatment as well as its costs.

By a further aspect the present invention provides a system for a virtual orthodontic treatment, comprising:

(a) storage means capable of storing a first virtual three-dimensional image indicative of a three-dimensional model of teeth of at least one, substantially entire jaw;

(b) user interface for enabling selection of a virtual set of orthodontic components;

(c) processor capable of at least:

(c1) manipulating said three-dimensional model to allow its viewing from a desired direction,

(c2) associating said set with the teeth of said first image to obtain a third image of said three-dimensional model with said components associated therewith, and

(c3) applying a set of rules, including at least one rule, determining effect of said components on the teeth so as to cause

virtual movement of the teeth as a result of association with said components to obtain a third teeth model; and

(d) display means for displaying the images.

5 Regardless of the aspect under consideration, the generation of virtual three-dimensional image may be obtained, e.g. by following the technique described in PCT Publication No. WO 97/03622, the contents of which is incorporated herein by reference.

10 By a still further aspect the present invention provides an apparatus having a memory which contains a digital image representing a three-dimensional teeth model following a virtual orthodontic treatment, which image was generated by any of the above methods.

By a further aspect there is provided a memory for storing data for access by an application program, implementing the steps (b)-(c) according to a method of each of the above aspects; the application program being executed on a data processing system; the data representing a first virtual three-dimensional image, indicative of the three-dimensional model of teeth of one jaw. Also provided is a memory for storing data representing a second virtual three-dimensional image, obtained by implementing the above method.

## 20 BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding, the invention will now be described by way of example only with reference to the annexed drawings in which:

Fig. 1 illustrates two components, a bracket and a wire, selectable by the user in a virtual treatment in accordance with one embodiment of the invention;

25 Fig. 2 is a cross-sectional view along line I-I in Fig. 2;

Fig. 3 is the same cross-sectional view as in Fig 2, after change in the slot angle;

Fig. 4 illustrates one view of user interface, according to an embodiment of the invention;

Fig. 5A is a block diagram illustrating the manner of defining a brackets for use in the framework of virtual treatment in accordance with an embodiment of the invention;

5 Figs. 5B-5D illustrate the brackets as viewed in various steps of the selection process;

Fig. 6A is a block diagram illustrating the manner of defining a wire for use within the framework of a virtual treatment in accordance with an embodiment of the invention;

10 Figs. 6B and Fig 6C illustrate the manner in which the wire is viewed in various steps of the process of Fig. 6a;

Fig. 7 is a block diagram illustrating the manner of attaching the brackets onto teeth in the virtual treatment, in accordance with an embodiment of the invention;

15 Fig. 8 is a block diagram illustrating the steps of matching wires to jaws and vertical movement of teeth to a position dictated by the wire;

Fig. 9 is a block diagram illustrating the steps of horizontal movement of teeth in the case of crowdnness, i.e. collision between teeth;

20 Fig. 10A is a block diagram illustrating the steps of matching wires to a jaw, in accordance with another embodiment of the invention, and movement of teeth as a result of virtual forces exerted by the wire or the teeth; and

Fig. 10B and 10C illustrate the manner in which the association between the wire and the teeth is viewed in two steps of the process of Fig. 10A.

## 25 DETAILED DESCRIPTION OF THE INVENTION

The present invention provides a method and system for virtual movement of teeth using the framework or a set of rules from which is based in real life, although not necessarily identical.

In the following, the invention may at times be described with a reference made to various physical entities, such as "jaw", "bracket", "wire", "band", etc. It should, however, be understood that it implies, in most cases, to a representation of these entities that is used in the virtual treatment. There are  
5 some exceptions where reference is made to real physical objects, which fact may clearly be inferred based on the context.

Teeth movement in a virtual, computerized 3D environment for the purpose of planning an orthodontic treatment or for any other purpose, is a complicated task if this is being performed using hitherto known techniques. The  
10 use of techniques known to the orthodont from a real orthodontic treatment, simplifies this virtual orthodontic treatment.

The virtual treatment may be required, at times, to allow the orthodont to determine a potential outcome of orthodontic treatment. For such a purpose, the virtual treatment need not necessarily follow a course to be followed  
15 by the real orthodontic treatment since the focus may be only on the final outcome, namely on the final position and orientation of the teeth following the treatment. In such a treatment, the orthodont may utilize orthodontic components and combination between such components, even such not used in real life orthodontic treatment. Examples are a selection of a wire with a different  
20 geometry than that used in real life or, change in the slot angle within the brackets so as to yield an angular moment on the teeth about the axis of the wire (see Fig. 3).

If, however, a virtual treatment is intended to simulate the real treatment for the purpose of treatment design, preferably (but not necessarily),  
25 only orthodontic components which simulate those used in real life orthodontic treatment, will be used.

In a typical yet not exclusive sequence of operation in virtual treatment, the user first selects brackets and places them at appropriate positions on the surface of selected teeth, usually all teeth of the jaw. In most cases

brackets are placed on the buccal teeth surface; however, occasionally, in the virtual treatment brackets may alternatively or additionally be placed on lingual surfaces of the teeth (this may also be followed at times in real life orthodontic treatment).

5           At a next step, the user may define the final desired distance between the teeth (the default is usually zero) and then selects an arch-wire from a library of such wires. The library may include wires of different widths, different cross-sectional shapes, and different geometries. Optionally, it is possible also to change the geometry of the selected wire, e.g. to make it to follow a tortuous path  
10       in a vertical and/or a horizontal plane, etc.

          Thereafter, the wire may be associated with the teeth model, for example, by combining them with virtual brackets fitted on the teeth surface or by attaching them first to virtual anchoring molars, and then to virtual brackets, etc. The effect of the components on each tooth is thereafter computed by the system,  
15       based on the set of rules to determine the outcome of the virtual treatment.

          If the virtual treatment uses components which simulate real-life components, once an optimal result of virtual treatment is reached, the parameters, namely the type of components which were used and the manner they were combined with one another and with the teeth model, may be recorded and  
20       this may then used to generate a prescription for the orthodontic treatment. Such a prescription may specify the type of components used, the exact position of each component, e.g. the position of the bracket on each tooth, etc.

          The virtual treatment may obviously also provide a tool to estimate the treatment length and costs.

25       The invention will now be further illustrated with reference to some specific, non-limiting embodiments, with reference to the annexed drawings.

          Figs. 1-3 show examples of a set of components which can be used in accordance with an embodiment of the invention. In this specific embodiment,

the components consist of a bracket 20 and wire 22 fixed on a surface of a tooth 24, of which only a portion thereof represented by a rectangle is seen. The user has freedom of choice of the exact position of attachment of the bracket 20 on the surface of the tooth 24 and also can slide wire 20 in a longitudinal axis within the receiving slot 26 of the bracket, as represented by the bi-directional arrow 28.

The wire and the bracket may be associated with one another in different relative orientations. In the example shown in Figs. 1 and 2, the wire, which in this case has a rectangular cross-section, is received in a slot with walls parallel and normal to the tooth's surface. By some embodiments of the invention it is possible to change the angle of slot 26 about its central axis, as represented by arrow 30, in Fig. 2 to yield a state such as that shown in Fig. 3, wherein wire 22' has a different angular orientation, with respect to bracket 20', thereby applying a moment onto tooth 24'.

Fig. 4 shows an example of an embodiment of one out of many possible variants of a user interface for realizing the initial component selection steps. The user can select the brackets from a library of brackets, and similarly can select wires, bands etc. from corresponding libraries. In addition, the user has the ability to determine the type of forces and their direction which will act on each tooth.

Fig. 5A illustrates the manner of defining a bracket for use in subsequent virtual treatment steps. In this process, the bracket is defined with respect to a relative coordinate system to allow its subsequent association with the wire, thus defining a "SLOT" frame of reference; (illustrated graphically in Figs. 5B and 5C) as well as to define another coordinate system to facilitate attachment of the bracket to the teeth, thus defining the "BOND" reference frame (illustrated graphically in Fig. 5D).

Although the steps of bracket definition are typically carried once, while creating the bracket library, it may also be repeated prior to each virtual treatment step while selecting brackets for the treatment.

Fig. 6A illustrates the steps of choosing a wire and defining it such that it can be subsequently used in the framework of virtual treatment. A wire is selected, its initial curve is defined (illustrated graphically in Fig. 6B) and then the wire is placed in a relative coordinate system (illustrated graphically in Fig. 6C), so as to define a "*WIRE*" frame of reference, for subsequent use. Obviously, as will be appreciated, the x-y-z coordinate system of the "*WIRE*" frame of reference should correspond to the x-y-z coordinate system of the "*SLOT*" reference frame.

Fig. 7 illustrates the steps of attachment of a bracket onto a tooth. A teeth model is acquired, brackets are selected from the library and each bracket is placed on a tooth using the "*BOND*" reference frame, such that the z axis of the BOND frame of reference is perpendicular to the surface. Once the bracket is placed at the desired location, it is both fixed in this location and then the process is repeated a plurality of times in accordance with the number of brackets to be placed on the teeth.

Fig. 8 illustrates the steps of matching the wires to the jaws. The wires are selected from a library, and placed so that their spline curve will match that of the jaw or their spline curve may at times be edited to amend it in accordance with the particulars' parameters of the jaw in a particular teeth model. In the specific Example shown, the process is first performed for the upper jaw and then for the lower jaw, although it will be appreciated that this sequence may be altered, e.g. reversed, performed intermittently in the upper and lower jaws, etc.

In this specific embodiment, the orientation and position of the wire dictates the final result, i.e. final alignment of all slots in the bracket. In other words, in this specific embodiment a set of rules applied in the virtual treatment includes, at minimum, a requirement for vertical realignment of the slots, and hence of the teeth to which they are attached, so that all slots will arrive to the wire. The set of rules also dictate how to accomplish this result. Put differently, as a result of the virtual treatment, in the final orientation which will be accomplished



in the resulting teeth model, the wire will remain at the same position and the teeth displaced such that the wire snaps into the slots of the bracket. This procedure is illustrated in Fig. 8., where the set of rules is dictated in blocks 81 and 82.

Another set of rules which can be applied in case of collision  
5 between the teeth, i.e. in case of crowding. This is illustrated in Fig. 9 where the teeth are moved horizontally by sliding along the wire, to avoid such collision. The manner in which the virtual treatment is performed may allow also some user intervention. For example, the user can define some teeth which may have to remain stationary, and others which are allowed to move. Alternatively, the  
10 system may have a wider degree of freedom, to allow sideways movement of all teeth. As also illustrated in Fig. 9, it is possible in this process to provide the user with an additional degree of freedom, which involves changing the position and/or orientation of the bracket on the tooth surface.

Fig. 10 illustrates another embodiment of teeth movement within  
15 the framework of a virtual treatment of the invention. As illustrated in Fig. 10A, wires are obtained, positioned in proximity of the jaw (illustrated graphically for the upper jaw in Fig. 10B), its shape edited so as to attach to the brackets on the teeth (illustrated graphically in Fig. 10C) and then the forces applied by the wire on the teeth are calculated and the final position of the teeth obtained can then be  
20 stored.

The present invention has been described with a certain degree of particularity but it should be understood that various modifications and alterations may be made without departing from the scope or spirit of the invention as defined by the following claims:

**CLAIMS:**

1. A method for virtual orthodontic treatment, comprising:

5 (a) providing a first virtual three-dimensional image indicative of a three-dimensional (3D) model of teeth from at least one jaw, the model being manipulable so as to allow its viewing from a desired direction;

(b) selecting a virtual set of orthodontic components, and associating the components with the teeth of said first image so as to obtain a second image of said 3D model with said components associated therewith;

10 (c) using a set of rules, including at least one rule, defining the effect of said set of components on said teeth, computing the manner of movement of the teeth as a result of said effect, so as to obtain a third image comprising the teeth model following the virtual treatment.

2. A method according to Claim 1, wherein steps (b) and (c) are  
15 repeated a plurality of times until obtaining a desired result of the virtual treatment.

3. A method for designing an orthodontic treatment of teeth from at least one jaw, comprising:

20 (a) providing a virtual three-dimensional image indicative of a three-dimensional model of the teeth in a manner allowing manipulation of the model for viewing the model from a desired direction;

(b) selecting a virtual set of orthodontic components corresponding to those intended to be used in said orthodontic treatment and associating the components with the teeth of said first image so as to obtain a second image of  
25 said three-dimensional model with said components associated therewith in a manner representing the manner in which said components and the teeth may be combined in said orthodontic treatment;

(c) using a set of rules, including at least one rule, defining the manner in which said components affect movement of the teeth, so as to obtain a third

image comprising the teeth model after movement of the teeth affected by said components;

(d) repeating steps (a) and (c) until a desired third image is obtained, which desired third image represents a desired position and orientation of teeth following the orthodontic treatment;

(e) recording said second image which yields, following step (c), the desired third image and using it as a basis for designing the orthodontic treatment.

4. A system for a virtual orthodontic treatment, comprising:

(a) storage means capable of storing a first virtual three-dimensional image indicative of a three-dimensional model of teeth of at least one, substantially entire jaw;

(b) user interface for enabling selection of a virtual set of orthodontic components;

(c) processor capable of at least:

(c1) manipulating said three-dimensional model to allow its viewing from a desired direction,

(c2) associating said set with the teeth of said first image to obtain a third image of said three-dimensional model with said components associated therewith, and

(c3) applying a set of rules, including at least one rule, determining effect of said components on the teeth so as to cause virtual movement of the teeth as a result of association with said components to obtain a third teeth model; and

(d) display means for displaying the images.

5. An apparatus having a memory which contains a digital image representing a three-dimensional teeth model following a virtual orthodontic treatment, which image is generated by the method of any one of Claims 1-3.

6. A memory for storing data for access by an application program implementing the steps (b)-(c) according to any one of Claims 1-3; the

application program being executed on a data processing system; the data representing a first three-dimensional image indicative of a three-dimensional.

1/9




FIG. 1




FIG. 2




FIG. 3

BAND		BRACKET		WIRE		VECTOR	
TOOTH							
UR	□ □ □ □ □	□ □ □ □ □	UL				
	5 4 3 2 1	1 2 3 4 5					
LR	□ □ □ □ □	□ □ □ □ □	LL				
<input type="button" value="Open"/>							

FIG. 4

2/9




FIG.5A

3/9




FIG. 5B




FIG. 5C




FIG. 5D

4/9




FIG.6A




FIG.6B




FIG.6C



5/9




FIG.7

6/9




FIG.8

7/9




FIG.9

8/9




FIG.10A

9/9




FIG. 10B




FIG. 10C

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/IL 98/00593

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC 6    A61C7/00    A61C7/12		
According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) IPC 6    A61C		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 94 10935 A (ORMCO CORP) 26 May 1994 see page 4, line 32-41 see page 5, line 39 - page 6, line 5 see figures 1,6,7C-8F ---	1-6
A	US 5 464 349 A (ANDREIKO CRAIG A ET AL) 7 November 1995 see column 5, line 48-60 see figure 16 -----	1-6
<input type="checkbox"/> Further documents are listed in the continuation of box C. <span style="margin-left: 100px;"><input checked="" type="checkbox"/> Patent family members are listed in annex.</span>		
* Special categories of cited documents : <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&amp;" document member of the same patent family</p> </div> </div>		
Date of the actual completion of the international search  <div style="text-align: center; font-weight: bold;">15 March 1999</div>		Date of mailing of the international search report  <div style="text-align: center; font-weight: bold;">24/03/1999</div>
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer  <div style="text-align: center; font-weight: bold;">Chabus, H</div>

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IL 98/00593

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9410935 A	26-05-1994	US 5368478 A	29-11-1994
		US 5447432 A	05-09-1995
		US 5454717 A	03-10-1995
		US 5431562 A	11-07-1995
		AU 5598894 A	08-06-1994
		EP 0667753 A	23-08-1995
		JP 8508174 T	03-09-1996
		US 5683243 A	04-11-1997
		US 5542842 A	06-08-1996
		US 5474448 A	12-12-1995
		US 5456600 A	10-10-1995
US 5464349 A	07-11-1995	US 5533895 A	09-07-1996